

ISUZU FTR 7m3 concrete mixer truck

Specification:

Basic parameters

Vehicle name:	7CBM concrete mixer truck	Brand	ISUZU FTR
engine:	QL1160VMFRY	Cab:	Row and half with sleeping cabin, Left Hand Driving
Gearbox:	ISUZU MLD 6 speeds	Rear axle:	13 ton rear axle
Dimensions:	7500×2500×3850(mm)	Actual volume:	7m3
Total mass:	18000kg	Quality of preparation:	9800kg
Top speed:	100km/h	Displacement:	5193ml
Wheelbase:	3900(mm)	Tire specifications:	10.00R20
Drive mode:	4×2	Braking method:	Steam brake (with ABS)
Fuel type:	Diesel oil	engine:	4HK1-TC50

Upload parameters

Head:	6mm thick high-strength manganese steel (Q345) material is more wear-resistant	Tank body:	5mm thick 16 Meng high alloy steel
blade:	4mm thick (520JJ) alloy steel material (add wear strip to increase service life)	Reducer:	PMP
Hydraulic system:	Sunny or Interpump	cooling system:	China famous brand
water supply system:	300L water tank air pressure water supply	Operation method:	Three-way operation on the left and right sides and the cab
Feeding speed:	3m3/min	Discharge speed:	2m3/min
Residual rate of discharge:	Residual rate of discharge ≤ 0.5	Unloading range:	180° up, down, left and right height adjustment